SPECaccel®2023 Result

Copyright 2023 Standard Performance Evaluation Corporation

NVIDIA Corporation
Tesla H100 96GB
MGX-GH200

SPECaccel 2023_base = 6.32

SPECaccel 2023_peak = 6.32

accel2023 License: 9045
Test Sponsor: NVIDIA Corporation
Tested by: NVIDIA Corporation

Test Date: Oct-2023
Hardware Availability: Sep-2023
Software Availability: Nov-2023



Hardware

CPU Name:	Grace
Max MHz.:	3100
Nominal:	2900
Enabled:	72 cores, 1 chip
Orderable:	1 chip
Cache L1:	64 KB I + 64 KB D on chip per core
L2:	1 MB I+D on chip per core
L3:	117 MB I+D on chip per chip
Other:	None
Memory:	480 GB (1 x 480 GB LPDDR5)
Storage:	1.8 TB NVMe
Other:	None
Base Threads Run:	1
Min. Peak Threads:	1
Max. Peak Threads:	1

Accelerator

Accel Model Name:	H100 96GB
Accel Vendor:	NVIDIA Corporation
Accel Name:	Tesla H100 96GB
Type of Accel:	GPU
Accel Connection:	NVLink-C2C
Does Accel Use ECC:	Yes
Accel Description:	Grace Hopper Superchip w/ 96GB device memory
Accel Driver:	NVIDIA UNIX Open Kernel Module for aarch64 525.105.17

Software

OS:	Ubuntu 22.04.3 LTS 6.2.0-1010-nvidia-64k
Compiler:	C/Fortran: Version 23.11 NVHPC SDK
Firmware:	NVIDIA 00010001 09/21/2023
File System:	ext4
System State:	Run level 3 (multi-user)
Other:	None
Base Parallel Model:	ACC
Base Threads Run:	1
Peak Parallel Models:	ACC

(Continued on next page)

SPECaccel®2023 Result

Copyright 2023 Standard Performance Evaluation Corporation

NVIDIA Corporation
Tesla H100 96GB
MGX-GH200

SPECaccel 2023_base = 6.32

SPECaccel 2023_peak = 6.32

accel2023 License: 9045
Test Sponsor: NVIDIA Corporation
Tested by: NVIDIA Corporation

Test Date: Oct-2023
Hardware Availability: Sep-2023
Software Availability: Nov-2023

Software (Continued)

Max. Peak Threads: 1
Min. Peak Threads: 1

Results Table

Benchmark	Base							Peak						
	Model	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
403.stencil	ACC	107	4.11	**107**	**4.10**			ACC	107	4.11	**107**	**4.10**		
404.lbm	ACC	63.3	7.19	**63.3**	**7.19**			ACC	63.3	7.19	**63.3**	**7.19**		
450.md	ACC	**172**	**3.49**	171	3.50			ACC	**172**	**3.49**	171	3.50		
452.ep	ACC	**88.1**	**4.71**	88.1	4.71			ACC	**88.1**	**4.71**	88.1	4.71		
453.clvrleaf	ACC	**90.7**	**11.0**	90.7	11.0			ACC	**90.7**	**11.0**	90.7	11.0		
455.seismic	ACC	136	5.75	**136**	**5.75**			ACC	136	5.75	**136**	**5.75**		
456.spF	ACC	71.8	6.62	**71.8**	**6.62**			ACC	71.8	6.62	**71.8**	**6.62**		
457.spC	ACC	102	5.30	**102**	**5.28**			ACC	102	5.30	**102**	**5.28**		
459.miniGhost	ACC	143	4.13	**143**	**4.12**			ACC	143	4.13	**143**	**4.12**		
460.ilbdc	ACC	**101**	**5.52**	100	5.52			ACC	**101**	**5.52**	100	5.52		
463.swim	ACC	28.7	15.3	**28.7**	**15.3**			ACC	28.7	15.3	**28.7**	**15.3**		
470.bt	ACC	**97.2**	**10.9**	97.0	10.9			ACC	**97.2**	**10.9**	97.0	10.9		

SPEC accel2023_base = 6.32

SPEC accel2023_peak = 6.32

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
Shell stacksize set to unlimited via "limit stacksize unlimited"
```

General Notes

```
Environment variables set by runaccel before the start of the run:
LD_LIBRARY_PATH = "/var/data0/sandbox/nvuser/SPECACCEL/nv239_libs"
Set to the location of the NVHPC compiler runtime libraries.


Submitted_by: Mathew Colgrove <mcolgrove@nvidia.com>
Submitted: Fri Oct 27 18:05:41 EDT 2023
Submission: accel2023-20231027-00009.sub
```

Platform Notes

```
 Sysinfo program /var/data0/sandbox/nvuser/mcolgrove/ACCELv2/bin/sysinfo
 Rev: r6622 of 2021-04-07 b1a7d5f8f71be5aff70a755cad7211a0
 running on LegoCG1-96GB-QS-102 Tue Oct 17 01:11:22 2023
```

(Continued on next page)

Platform Notes (Continued)

```
SUT (System Under Test) info as seen by some common utilities.
For more information on this section, see
   https://www.spec.org/cpu2017/Docs/config.html#sysinfo

From /proc/cpuinfo
*
* Did not identify cpu model.  If you would
* like to write your own sysinfo program, see
* www.spec.org/cpu2017/config.html#sysinfo
*
*
* 0 "physical id" tags found.  Perhaps this is an older system,
* or a virtualized system.  Not attempting to guess how to
* count chips/cores for this system.
*
      72 "processors"
   cores, siblings (Caution: counting these is hw and system dependent. The following
   excerpts from /proc/cpuinfo might not be reliable.  Use with caution.)

From lscpu from util-linux 2.37.2:
     Architecture:                         aarch64
     CPU op-mode(s):                       64-bit
     Byte Order:                           Little Endian
     CPU(s):                               72
     On-line CPU(s) list:                  0-71
     Vendor ID:                            ARM
     Model:                                0
     Thread(s) per core:                   1
     Core(s) per socket:                   72
     Socket(s):                            1
     Stepping:                             r0p0
     Frequency boost:                      disabled
     CPU max MHz:                          3429.0000
     CPU min MHz:                          81.0000
     BogoMIPS:                             2000.00
     Flags:                                fp asimd evtstrm aes pmull sha1 sha2 crc32
     atomics fphp asimdhp cpuid asimdrdm jscvt fcma lrcpc dcpop sha3 sm3 sm4 asimddp
     sha512 sve asimdfhm dit uscat ilrcpc flagm ssbs sb paca pacg dcpodp sve2 sveaes
     svepmull svebitperm svesha3 svesm4 flagm2 frint svei8mm svebf16 i8mm bf16 dgh bti
     L1d cache:                            4.5 MiB (72 instances)
     L1i cache:                            4.5 MiB (72 instances)
     L2 cache:                             72 MiB (72 instances)
     L3 cache:                             114 MiB (1 instance)
     NUMA node(s):                         9
     NUMA node0 CPU(s):                    0-71
     NUMA node1 CPU(s):
     NUMA node2 CPU(s):
```

(Continued on next page)

Platform Notes (Continued)

```
      NUMA node3 CPU(s):
      NUMA node4 CPU(s):
      NUMA node5 CPU(s):
      NUMA node6 CPU(s):
      NUMA node7 CPU(s):
      NUMA node8 CPU(s):
      Vulnerability Gather data sampling: Not affected
      Vulnerability Itlb multihit:        Not affected
      Vulnerability L1tf:                 Not affected
      Vulnerability Mds:                  Not affected
      Vulnerability Meltdown:             Not affected
      Vulnerability Mmio stale data:      Not affected
      Vulnerability Retbleed:             Not affected
      Vulnerability Spec store bypass:    Mitigation; Speculative Store Bypass disabled
      via prctl
      Vulnerability Spectre v1:           Mitigation; __user pointer sanitization
      Vulnerability Spectre v2:           Not affected
      Vulnerability Srbds:                Not affected
      Vulnerability Tsx async abort:      Not affected

  From lscpu --cache:
      NAME ONE-SIZE ALL-SIZE WAYS TYPE        LEVEL   SETS PHY-LINE COHERENCY-SIZE
      L1d       64K     4.5M    4 Data            1    256                    64
      L1i       64K     4.5M    4 Instruction     1    256                    64
      L2         1M      72M    8 Unified         2   2048                    64
      L3       114M     114M   12 Unified         3 155648                    64

  From numactl --hardware
  WARNING: a numactl 'node' might or might not correspond to a physical chip.
    available: 9 nodes (0-8)
    node 0 cpus: 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27
    28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56
    57 58 59 60 61 62 63 64 65 66 67 68 69 70 71
    node 0 size: 490308 MB
    node 0 free: 76775 MB
    node 1 cpus:
    node 1 size: 97280 MB
    node 1 free: 96957 MB
    node 2 cpus:
    node 2 size: 0 MB
    node 2 free: 0 MB
    node 3 cpus:
    node 3 size: 0 MB
    node 3 free: 0 MB
    node 4 cpus:
    node 4 size: 0 MB
    node 4 free: 0 MB
```

(Continued on next page)

Platform Notes (Continued)

```
   node 5 cpus:
   node 5 size: 0 MB
   node 5 free: 0 MB
   node 6 cpus:
   node 6 size: 0 MB
   node 6 free: 0 MB
   node 7 cpus:
   node 7 size: 0 MB
   node 7 free: 0 MB
   node 8 cpus:
   node 8 size: 0 MB
   node 8 free: 0 MB
   node distances:
   node   0   1   2   3   4   5   6   7   8
     0:  10  80  80  80  80  80  80  80  80
     1:  80  10  255  255  255  255  255  255  255
     2:  80  255  10  255  255  255  255  255  255
     3:  80  255  255  10  255  255  255  255  255
     4:  80  255  255  255  10  255  255  255  255
     5:  80  255  255  255  255  10  255  255  255
     6:  80  255  255  255  255  255  10  255  255
     7:  80  255  255  255  255  255  255  10  255
     8:  80  255  255  255  255  255  255  255  10

From /proc/meminfo
   MemTotal:       601690240 kB
   HugePages_Total:       0
   Hugepagesize:     524288 kB

/sys/devices/system/cpu/cpu*/cpufreq/scaling_governor has
   performance

/usr/bin/lsb_release -d
   Ubuntu 22.04.3 LTS

From /etc/*release* /etc/*version*
   debian_version: bookworm/sid
   l4t-release:
      L4T_NAME="L4T Server"
      L4T_PRETTY_NAME="NVIDIA L4T Server"
      L4T_SWBUILD_DATE="2023-09-12-19-18-30"
      L4T_SWBUILD_VERSION="6.0.0-nvidia"
      L4T_COMMIT_ID="3244539"
      L4T_PLATFORM=""
      L4T_SERIAL_NUMBER=""
   os-release:
      PRETTY_NAME="Ubuntu 22.04.3 LTS"
```

(Continued on next page)

Platform Notes (Continued)

```
       NAME="Ubuntu"
       VERSION_ID="22.04"
       VERSION="22.04.3 LTS (Jammy Jellyfish)"
       VERSION_CODENAME=jammy
       ID=ubuntu
       ID_LIKE=debian
       HOME_URL="https://www.ubuntu.com/"

uname -a:
   Linux LegoCG1-96GB-QS-102 6.2.0-1010-nvidia-64k #10-Ubuntu SMP PREEMPT_DYNAMIC Wed Aug
   30 06:23:50 UTC 2023 aarch64 aarch64 aarch64 GNU/Linux

Kernel self-reported vulnerability status:

gather_data_sampling:                                  Not affected
CVE-2018-12207 (iTLB Multihit):                        Not affected
CVE-2018-3620 (L1 Terminal Fault):                     Not affected
Microarchitectural Data Sampling:                      Not affected
CVE-2017-5754 (Meltdown):                              Not affected
mmio_stale_data:                                       Not affected
retbleed:                                              Not affected
CVE-2018-3639 (Speculative Store Bypass):              Mitigation: Speculative Store
                                                       Bypass disabled via prctl
CVE-2017-5753 (Spectre variant 1):                     Mitigation: __user pointer
                                                       sanitization
CVE-2017-5715 (Spectre variant 2):                     Not affected
CVE-2020-0543 (Special Register Buffer Data Sampling): Not affected
CVE-2019-11135 (TSX Asynchronous Abort):               Not affected

run-level 3 Oct 14 00:07

SPEC is set to: /var/data0/sandbox/nvuser/mcolgrove/ACCELv2
   Filesystem     Type  Size  Used Avail Use% Mounted on
   /dev/nvme0n1p2 ext4  1.8T  1.5T  200G  89% /

Cannot run dmidecode; consider saying (as root)
   chmod +s /usr/sbin/dmidecode

BIOS:
   BIOS Vendor:       NVIDIA
   BIOS Version:              00010001
   BIOS Date:         20230921

(End of data from sysinfo program)
```

Compiler Version Notes

```
==============================================================================
C          | 403.stencil(base) 404.lbm(base) 452.ep(base) 470.bt(base)
------------------------------------------------------------------------------
nvc Rel Dev-r238862 linuxarm64 target on aarch64 Linux -tp neoverse-v2
NVIDIA Compilers and Tools
Copyright (c) 2023, NVIDIA CORPORATION & AFFILIATES.  All rights reserved.
------------------------------------------------------------------------------

==============================================================================
C          | 457.spC(base)
------------------------------------------------------------------------------
nvc-Warning-Only small, tiny and large code models are allowed on AArch64.
  The code model large will be used.
/usr/bin/ld: /usr/lib/aarch64-linux-gnu/crt1.o: in function ‘__wrap_main’:
(.text+0x38): undefined reference to ‘main’
pgacclnk: child process exit status 1: /usr/bin/ld
nvc Rel Dev-r238862 linuxarm64 target on aarch64 Linux -tp neoverse-v2
NVIDIA Compilers and Tools
Copyright (c) 2023, NVIDIA CORPORATION & AFFILIATES.  All rights reserved.
------------------------------------------------------------------------------

==============================================================================
C          | 403.stencil(base) 404.lbm(base) 452.ep(base) 470.bt(base)
------------------------------------------------------------------------------
nvc Rel Dev-r238862 linuxarm64 target on aarch64 Linux -tp neoverse-v2
NVIDIA Compilers and Tools
Copyright (c) 2023, NVIDIA CORPORATION & AFFILIATES.  All rights reserved.
------------------------------------------------------------------------------

==============================================================================
C          | 457.spC(base)
------------------------------------------------------------------------------
nvc-Warning-Only small, tiny and large code models are allowed on AArch64.
  The code model large will be used.
/usr/bin/ld: /usr/lib/aarch64-linux-gnu/crt1.o: in function ‘__wrap_main’:
(.text+0x38): undefined reference to ‘main’
pgacclnk: child process exit status 1: /usr/bin/ld
nvc Rel Dev-r238862 linuxarm64 target on aarch64 Linux -tp neoverse-v2
NVIDIA Compilers and Tools
Copyright (c) 2023, NVIDIA CORPORATION & AFFILIATES.  All rights reserved.
------------------------------------------------------------------------------

==============================================================================
Fortran    | 450.md(base) 455.seismic(base) 456.spF(base) 460.ilbdc(base)
           | 463.swim(base)
------------------------------------------------------------------------------
nvfortran Rel Dev-r238862 linuxarm64 target on aarch64 Linux -tp neoverse-v2
```

(Continued on next page)

Compiler Version Notes (Continued)

```
NVIDIA Compilers and Tools
Copyright (c) 2023, NVIDIA CORPORATION & AFFILIATES.  All rights reserved.
------------------------------------------------------------------------------

==============================================================================
Fortran, C | 453.clvrleaf(base) 459.miniGhost(base)
------------------------------------------------------------------------------
nvfortran Rel Dev-r238862 linuxarm64 target on aarch64 Linux -tp neoverse-v2
NVIDIA Compilers and Tools
Copyright (c) 2023, NVIDIA CORPORATION & AFFILIATES.  All rights reserved.
nvc Rel Dev-r238862 linuxarm64 target on aarch64 Linux -tp neoverse-v2
NVIDIA Compilers and Tools
Copyright (c) 2023, NVIDIA CORPORATION & AFFILIATES.  All rights reserved.
------------------------------------------------------------------------------
```

Base Compiler Invocation

C benchmarks:
nvc

Fortran benchmarks:
nvfortran

Benchmarks using both Fortran and C:
nvfortran nvc

Base Portability Flags

403.stencil: No flags used
404.lbm: No flags used
450.md: No flags used
452.ep: No flags used
453.clvrleaf: No flags used
455.seismic: No flags used
456.spF: No flags used
457.spC: -mcmodel=medium -Wl,--no-relax
459.miniGhost: No flags used
460.ilbdc: No flags used
463.swim: No flags used
470.bt: No flags used

Base Optimization Flags

C benchmarks:
`-Ofast -acc -Mfprelaxed -Mstack_arrays -static-nvidia -march=neoverse-v2`

Fortran benchmarks:
`-Ofast -acc -Mfprelaxed -Mstack_arrays -static-nvidia -march=neoverse-v2`

Benchmarks using both Fortran and C:

453.clvrleaf: `-Ofast -acc -Mfprelaxed -Mstack_arrays -static-nvidia -march=neoverse-v2`

459.miniGhost: `-Mnomain -Ofast -acc -Mfprelaxed -Mstack_arrays -static-nvidia -march=neoverse-v2`

Peak Optimization Flags

C benchmarks:

403.stencil: `basepeak = yes`

404.lbm: `basepeak = yes`

452.ep: `basepeak = yes`

457.spC: `basepeak = yes`

470.bt: `basepeak = yes`

Fortran benchmarks:

450.md: `basepeak = yes`

455.seismic: `basepeak = yes`

456.spF: `basepeak = yes`

460.ilbdc: `basepeak = yes`

463.swim: `basepeak = yes`

Benchmarks using both Fortran and C:

(Continued on next page)

Peak Optimization Flags (Continued)

453.clvrleaf: `basepeak = yes`

459.miniGhost: `basepeak = yes`

The flags file that was used to format this result can be browsed at
`https://pro.spec.org/private/hpg/submit/accel2023/flags/nv2023_flags_v2_arm.html`

You can also download the XML flags source by saving the following link:
`https://pro.spec.org/private/hpg/submit/accel2023/flags/nv2023_flags_v2_arm.xml`

SPECaccel is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPECaccel2023 v2.0.17 on 2023-10-16 21:11:22-0400.
Report generated on 2023-11-08 13:07:37 by accel2023 PS formatter v112.
Originally published on 2023-11-08.